

# CPS SCH275KTL-DO/EU

Three Phase String Inverter  
275kW / 6/12 MPPTs / 1500Vdc System



## Efficient

Higher power generation

- 6/12 MPPTs with Max. Efficiency 99%.
- Max. input current 20A per string, compatible with 600Wp+ module.
- Superb temperature performance, full power at 42°C.
- Compatible with cables up to 400mm<sup>2</sup>.



## Smart

Fully controllable

- Comprehensive range of communication interfaces [PLC / Wi-Fi / RS485 (Standard) & 4G / Ethernet(Optional)].



## Safe

Superior quality with fast response

- Durable and robust component.
- Artfully designed air forced cooling system.
- IP66&C5 protection.
- Type II SPD for both DC and AC.
- Full range of grid monitoring and protection.
- Built-in anti-PID and PID recovery function.

# CPS SCH275KTL-DO/EU

Three Phase String Inverter  
275kW / 6/12 MPPTs / 1500Vdc  
System



Model Name	CPS SCH275KTL-DO/EU	
<b>DC Input</b>		
Max. DC Voltage	1500Vdc	
MPPT Operating Voltage Range	500-1450Vdc	
Start Voltage	550Vdc	
Rated DC Voltage	1190Vdc	
Number of MPPT	12	6
Number of DC Connection Sets per MPPT	2	3
Max. Input Current per MPPT	30A	60A
Max. DC Short-Circuit Current per MPPT	50A	90A
String Fuse	/	25A
DC Disconnection Type	Integrated Switch	
<b>AC Output</b>		
Rated AC Power	275kW	
Max. AC Power	275kVA	
Rated AC Voltage	800V	
AC Voltage Range	680 - 880Vac	
Grid Connection Type	3Φ / PE (IT system <sup>1</sup> )	
Max. AC Current	198.5A	
Grid Frequency	50/60Hz	
Grid Frequency Range	47-53/57-63Hz	
Power Factor (cosφ)	>0.99 (0.8 Adjustable)	
Current THD	< 3%	
AC Disconnection Type	/	
<b>System Data</b>		
Topology	Transformerless	
Max. Efficiency	99,0%	
Euro Efficiency	98,5%	
<b>Protection</b>		
DC Reverse Connection Protection	Yes	
AC Short Circuit Protection	Yes	
Leakage Current Protection	Yes	
Grid Monitoring	Yes	
Ground Fault Monitoring	Yes	
Surge Protection	DC Type II / AC Type II	
AFCI	/	
<b>Environment Data</b>		
Ingress Protection	IP66	
Cooling Method	Cooling Fans	
Operating Temperature	-30°C to +60°C	
Ambient Humidity	0 - 100%	
Altitude	4000m	
<b>Display and Communication</b>		
Display	LED + APP (Bluetooth)	
Communication	PLC / Wi-Fi / RS485(Standard) & 4G / Ethernet (Optional)	
<b>Mechanical Data</b>		
Dimensions (W*H*D)	1100 * 680 * 337mm	
Weight	105kg	
DC Connection Type	MC4 (Max. 6 mm <sup>2</sup> )	
AC Connection Type	OT/DT Terminal (Max. 300 mm <sup>2</sup> )	
<b>Safety</b>		
Certifications <sup>2</sup>	IEC61000-6, IEC/EN 62109, IEC61727/62116/61683/60068, EN50549, NC RfG, NTS_V2.1	

<sup>1</sup> Transformer compatibility: this model only supports connection with IT systems, not compatible with TN/TT systems.

<sup>2</sup> AC Power is different under different rated AC voltage.

<sup>3</sup> The certificates are for reference only. Please consult the local sales staff for detailed certification.